

## TR-110



# TR-110 Surface roughness tester



## Features

- Both Ra and Rz parameters in one instrument
- LCD with backlight, dynamic test display: progress bar gives indication of measuring process
- Protection slide on pick-up
- Auto-off after 90 seconds
- Software calibration
- Large measuring range suitable for most materials
- Piëzo-electric pick-up stylus for external surfaces
- Li-ion rechargeable battery
- Sound signal start-test-ready
- Standard conform to ISO and DIN

## Technical specifications

Roughness parameter	Ra, Rz
Units	$\mu\text{m}$ / $\mu\text{inch}$
Measuring range	Ra: 0.05 $\mu\text{m}$ - 10.0 $\mu\text{m}$ , Rz: 0.1 $\mu\text{m}$ - 50 $\mu\text{m}$
Cut-off lengths	0.25mm, 0.8mm, 2.5mm
Evaluation length	1.25mm/4.0mm/5.0mm
Filter	RC analogue
Functions	Dynamic display during testing, sound signal start-test-ready, auto-off 90 seconds, backlight LCD
Calibration	By CAL function
Min. curvature of cylindrical surface	40mm diameter (V-grooved base)
Tracing length	6mm
Tracing speed	1.0mm/sec
Accuracy	< $\pm$ 15% , Conforms to ISO Class 3
Pick-up stylus	Piëzo-electric
Tracer tip	Diamond, radius : 10 $\pm$ 2.5 $\mu\text{m}$ , Angle: 90° (+5°or -10°)
Ventilation	Grade 3
Operating temperature	0°C - 40°C
Power	3.6 V / Li-ion battery low battery indication
Charger	6V DC (rechargeable while working)
Dimensions	110mm x 70mm x 24mm
Weight	200gr

## Standard delivery

- Instrument
- Protection cover for tracer
- Roughness test plate Ra
- Charger
- Carrying case
- Manual
- INNOVATEST® certificate

## Optional accessories

- UKAS certified roughness test plates



## Order details

**TR-110** Surface roughness tester for external surfaces and grooves with LCD backlight display

Represented by:

IN10-208 130215

## CORPORATE HEAD OFFICE

### **INNOVATEST Europe BV** **MANUFACTURING, DISTRIBUTION & SERVICE**

Borgharenweg 140  
6222 AA Maastricht (The Netherlands)  
Phone: +31 43 3520060  
Fax: +31 43 3631168  
E-mail: [info@innovatest-europe.com](mailto:info@innovatest-europe.com)  
Website: [www.innovatest-europe.com](http://www.innovatest-europe.com)

---

## BRANCHE OFFICES

### **INNOVATEST Benelux BVBA** **SALES & SERVICE**

Phone: +32 12 779002  
Fax: +32 12 779003  
E-mail: [info@innovatest-benelux.com](mailto:info@innovatest-benelux.com)  
Website: [www.innovatest-europe.com](http://www.innovatest-europe.com)

### **INNOVATEST Shanghai Co., Ltd.** **ASIA & CHINA SALES & SERVICE**

Building 2, No.123, 1165 Nong Jindu Road,  
South Metropolis Industrial Park  
Minhang District, Shanghai, P.R. China  
Zip code: 201108  
E-mail: [info@innovatest-shanghai.com](mailto:info@innovatest-shanghai.com)  
Website: [www.innovatest-shanghai.com](http://www.innovatest-shanghai.com)

Changes in products and/or product specifications can emerge due to new technologies and continuous development.

We reserve the right to change or modify specifications of products without prior notice.

We recommend you to contact our sales office for up-to-date information.

© All rights reserved